

Product Description

The BSW6620 is an absorptive SPDT 50Ω matched RF switch supporting bandwidth up to 9GHz. It's high linearity performance across the temperature range makes it ideally suitable for use in 3G/4G/5G/6G wireless infrastructure and 802.11 a/n/ac/ax applications where high isolation and excellent performance is required.

The BSW6620 is designed with robust ESD protection circuits at all pins and packaged in an industry standard, fully RoHS2-compliant, 16Lead, 4mm x 4mm x 0.9mm QFN package.

The BSW6620 does not require blocking capacitors. If DC is presented at the RF port, add a blocking capacitor.

A functional block diagram is shown in Figure 1.

Block Diagram




Figure 1. Functional Block Diagram

Applications

- Wireless 3G/4G/5G/6G Infrastructure
- Base station & Repeater
- WLAN 802.11 a/b/ac/ax

Package Type



4mm x 4mm x 0.9mm, 16-Lead QFN Package

Figure 2. Package type

Device Features

- Supply Voltage : 2.7V to 5.5V
- Low Insertion Loss
 - : 0.72dB @ 2GHz
 - : 0.83dB @ 4GHz
 - : 0.74dB @ 6GHz
 - : 1.02dB @ 7.2GHz
- Ultra High Isolation
 - RFC to RFx
 - : 65dB @ 2GHz
 - : 58dB @ 4GHz
 - : 54dB @ 6GHz
 - : 49dB @ 7.2GHz
 - RFx to RFx
 - : 56dB @ 2GHz
 - : 50dB @ 4GHz
 - : 46dB @ 6GHz
 - : 42dB @ 7.2GHz
- Switching time : 120 to 240ns
- ESD, HBM : ±2.0kV @All pins
- Operating temperature range : -40°C to +105°C

Electrical Specifications

Typical conditions are at VDD = 5V, T_A = +25°C, VCTL/EN Low = 0V, VCTL/EN High = 3.3V, Z_L = 50Ω, excluding SMA Connector and PCB losses⁽¹⁾, unless otherwise noted.

Table 1. Electrical Specifications

Parameter	Path	Condition	Min	Typ	Max	Unit
Operating Frequency			5		9000	MHz
Insertion Loss	RFC - RFx	1GHz		0.61		dB
		2GHz		0.72		
		3GHz		0.96		
		4GHz		0.83		
		5GHz		0.79		
		6GHz		0.74		
		7GHz		0.88		
		8GHz		1.04		
		9GHz		1.80		
Isolation (C to X)	RFC - RFx	1GHz		75		dB
		2GHz		70		
		3GHz		61		
		4GHz		56		
		5GHz		54		
		6GHz		53		
		7GHz		50		
		8GHz		45		
		9GHz		44		
Isolation (X to X)	RFx - RFx	1GHz		61		dB
		2GHz		55		
		3GHz		52		
		4GHz		49		
		5GHz		46		
		6GHz		44		
		7GHz		42		
		8GHz		40		
		9GHz		39		
Return Loss (Active Port)	RFC / RF1 / RF2	5MHz–2GHz		23 / 21 / 21		dB
		2GHz–5GHz		15 / 15 / 15		
		5GHz–8GHz		20 / 20 / 15		
		8GHz–9GHz		10 / 10 / 10		
Return Loss (Terminated Port)	RFC / RF1 / RF2	5MHz–2GHz		25 / 17 / 17		dB
		2GHz–5GHz		15 / 15 / 15		
		5GHz–8GHz		20 / 15 / 15		
		8GHz–9GHz		10 / 12 / 12		
Switching time	RFC - RFx	50% CTRL to 90% RF		240		ns
		50% CTRL to 10% RF		120		
Settling time	RFC - RFx	50% CTRL to 0.05dB final value Rising Edge		320		ns
		50% CTRL to 0.05dB final value Falling Edge		150		

(1)Excluding SMA Connector and PCB loss.

1GHz (0.24dB), 2GHz (0.34dB), 3GHz (0.37dB), 4GHz (0.49dB), 5GHz (0.49dB), 6GHz (0.68dB), 7GHz (0.78dB), 8GHz (0.73dB), 9GHz (0.82dB)

Electrical Specifications

Typical conditions are at VDD = 5V, T_A = +25°C, VCTL/EN Low = 0V, VCTL/EN High = 3.3V, Z_L = 50Ω, excluding SMA Connector and PCB losses⁽¹⁾, unless otherwise noted.


Table 1. Electrical Specifications (Cont.)

Parameter	Path	Condition	Min	Typ	Max	Unit
Operating Frequency			5		9000	MHz
Input P1dB	RFC - RFx	2.35GHz 3.5GHz 4.9GHz		36.5 35.7 35.8		dBm
Input IP2 ⁽²⁾	RFC - RFx	2.35GHz 3.5GHz 4.9GHz		112 107 102		dBm
Input IP3 ⁽²⁾	RFC - RFx	2.35GHz 3.5GHz 4.9GHz		66 68 65		dBm
2nd Harmonics ⁽³⁾	RFC - RFx	2.35GHz 3.5GHz 4.9GHz		100 95 92		dBc
3rd Harmonics ⁽³⁾	RFC - RFx	2.35GHz 3.5GHz 4.9GHz		101 105 96		dBc
Maximum Spurious Level	RFC - RFx	5MHz–9GHz ⁽⁴⁾		<-145		dBm/10Hz

(2)The each-tone Power is 20dBm and Tone spacing is 1MHz.

(3)Tone Power is 20dBm.

(4)No spurious signals were detected in all Frequency range.

Product Description

Figure 3. Pin Description (Top View)
Table 2. Pin Descriptions

Pin No.	Pin Name	Description
1	VDD	Supply Voltage.
2	VCTL	Switch Control Input. (Referring to Table 3)
3	RFC	RFC Port.
4, 6, 7, 8, 10, 11, 13, 14, 15	GND	Ground.
5	EN	Switch Control Input. (Definition for the EN pin, See Table 3)
9	RF1	RF1 Port.
12	RF2	RF2 Port.
16	N/C	Internal connection to Ground, External connection to PCB Ground Recommended to maximize isolation.
Pad	Exposed Pad	Ground.

Table 3. Control Truth Table

VCTL	EN	RFC-RF1	RFC-RF2
1	0	ON	OFF
0	0	OFF	ON
0	1	OFF	OFF
1	1	OFF	OFF

Table 4. Operating Ranges

Parameter	Symbol	Min	Typical	Max	Unit
Supply Voltage	VDD	2.7		5.5	V
Supply Current	IDD	-	210	-	μA
Digital Input Control (VCTL/EN)	V _L High	1.0	-	3.3	V
	V _L Low	0	-	0.7	V
Operating Temperature Range	T _O	-40	+25	+105	°C
RF Input Power, CW	P _{CWOP}	-	-	33	dBm

Table 5. Absolute Maximum Ratings

Parameter		Symbol	Min	Max	Unit
Supply Voltage		VDD	-0.3	5.5	V
Digital Input Voltage		VCTL / EN	-0.3	3.6	V
Maximum Input Power, CW (+25°C)		RF _{CWMAX}	-	Input P1dB	dBm
Storage Temperature Range		T _{ST}	-65	+150	°C
ESD	HBM	ALL pins	V _{ESDHBM}	±2000	V
	CDM	ALL pins	V _{ESDCDM}	±1000	V

Table 6. Package Thermal Characteristics

Parameter	Symbol	Value	Unit
Junction to Ambient Thermal Resistance	θ_{JA}	43.2	°C/W

Typical Performances

Typical conditions are at VDD = 5V, T_A = 25°C, VCTL/EN Low = 0V, VCTL/EN High = 3.3V, Z_L = 50Ω, Excluding SMA Connector and PCB losses, unless otherwise noted.

Figure 4. Insertion Loss vs VDD [RFC to RF1]




Figure 5. Insertion Loss vs VDD [RFC to RF2]




Figure 6. Insertion Loss vs Temp [RFC to RF1]




Figure 7. Insertion Loss vs Temp [RFC to RF2]




Figure 8. RFC Port Return Loss vs Temp [RF1 On state]











Figure 9. RFC Port Return Loss vs Temp [RF2 On state]



Typical Performances

Typical conditions are at VDD = 5V, T_A = 25°C, VCTL/EN Low = 0V, VCTL/EN High = 3.3V, Z_L = 50Ω, Excluding SMA Connector and PCB losses, unless otherwise noted.

Figure 10. RF1 Port Return Loss vs Temp [On state]

Figure 11. RF2 Port Return Loss vs Temp [On state]

Figure 12. RF1 Port Return Loss vs Temp [Off state]

Figure 13. RF2 Port Return Loss vs Temp [Off state]

Figure 14. Isolation vs VDD [RFC to RFx]

Figure 15. Isolation vs Temp [RFC to RFx]


Typical Performances

Typical conditions are at VDD = 5V, T_A = 25°C, VCTL/EN Low = 0V, VCTL/EN High = 3.3V, Z_L = 50Ω, Excluding SMA Connector and PCB losses, unless otherwise noted.

Figure 16. Isolation vs VDD [RFx to RFx]




Figure 17. Isolation vs Temp [RFx to RFx]




Figure 18. Input IP2 vs VDD [RFC to RFx]




Figure 19. Input IP2 vs Temp [RFC to RFx]




Figure 20. Input IP3 vs VDD [RFC to RFx]





Figure 21. Input IP3 vs Temp [RFC to RFx]



Typical Performances

Typical conditions are at VDD = 5V, T_A = 25°C, VCTL/EN Low = 0V, VCTL/EN High = 3.3V, Z_L = 50Ω, Excluding SMA Connector and PCB losses, unless otherwise noted.

Figure 22. 2nd Harmonic vs VDD [RFC to RFx]




Figure 23. 2nd Harmonic vs Temp [RFC to RFx]




Figure 24. 3rd Harmonic vs VDD [RFC to RFx]




Figure 25. 3rd Harmonic vs Temp [RFC to RFx]




Figure 26. Input P1dB vs VDD [RFC to RFx]





Figure 27. Input P1dB vs Temp [RFC to RFx]



Evaluation Board




Figure 28. Evaluation Board Layout







Figure 29. Evaluation Board Schematic

Table 7. Bill of Material - Evaluation Board

No.	Ref Des	Part Qty	Part Number	Remark
1	C1	1	CAP 1005 1uF J 50V	
2	C5	1	CAP 1005 100nF J 50V	
3	C6	1	CAP 1005 100pF J 50V	
4	C2,C3,C4,C7,C8,C9	6	CAP 1005 DNI	
5	R1,R2,R3	3	RES 1005 0 ohm	
6	J1,J2,J3	3	2 Pin Header 2.54mm	
7	S1,S2,S3,S4,S5	5	SMA_END_LAUNCH	
8	U1	1	BSW6620	

Evaluation Board

Figure 30. Suggested PCB Land Pattern

Figure 31. Evaluation Board PCB Layer Information


Package Outline Drawing

NOTES:

1. Dimensioning and tolerancing conform to ASME Y14.5–2009.
2. All dimensions are in millimeters.
3. N is the total number of terminals.
4. The location of the marked terminal #1 identifier is within the hatched area.
5. ND and NE refer to the number of terminals each D and E side respectively.
6. Dimension b applies to the metallized terminal and is measured between 0.15mm and 0.3mm from the terminal tip. If the terminal has a radius on the other end of it, dimension b should not be measured in that radius area.
7. Coplanarity applies to the terminals and all other bottom surface metallization.


Dimension Table					
Symbol	Thickness	Min	Nominal	Max	Note
A		0.80	0.90	1.00	
A1		0.00	0.02	0.05	
A3		---	0.203 Ref.	---	
b		0.25	0.30	0.35	6
D		4.00 BSC			
E		4.00 BSC			
e		0.65 BSC			
D2		2.35	2.40	2.45	
E2		2.35	2.40	2.45	
K		0.20	---	---	
L		0.45	0.55	0.65	
aaa		0.05			
bbb		0.10			
ccc		0.10			
dad		0.05			
eee		0.08			
N		16			3
ND		4			5
NE		4			5
NOTES		1,2			

Figure 32. Package Outline Dimension

Tape & Reel



TYPE	A	N	C	D	w1	w2	w3	T	k
12MM	$\varnothing 180^{+2}_{-2}$	$\varnothing 60^{+1}_{-1}$	$\varnothing 13.1^{+0.2}_{-0.2}$	4.2±0.5	12.5 ⁺¹ ₋₀	15.7 ⁺¹ ₋₁	12.7 ⁺¹ ₋₁	1.5±0.15	1.2±0.1



NOTES:
 1 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE ±0.2
 2 CAMBER IN COMPLIANCE WITH EIA 481
 3 POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE

Packaging information:	
Tape Width	12mm
Reel Size	7inch
Device Cavity Pitch	8mm
Device Per Reel	1000EA

Figure 33. Tape & Reel Information

Package Marking


Marking information:	
BSW6620	Device Name
YY	Year
WW	Work Week
XX	Wafer Lot Number

Figure 34. Package Marking
Lead plating finish
100% Tin Matte finish

(All BeRex products undergoes a 1 hour, 150 degree C, Anneal bake to eliminate thin whisker growth concerns.)

MSL / ESD Rating

ESD information1 :	
Rating	Class 2 ($\pm 2000V$)
Test	Human Body Model (HBM)
Standard	JEDEC Standard JS-001-2017

ESD information2 :	
Rating	Class C3 ($\pm 1000V$)
Test	Charged Device Model (CDM)
Standard	JEDEC Standard JS-002-2018

MSL information:	
Rating	Level 1 at +260°C convection reflow
Standard	JEDEC Standard J-STD-020



Proper ESD procedures should be followed when handling the device.

RoHS Compliance

This part is compliant with Restrictions on the use of certain Hazardous Substances in Electrical and Electronic Equipment (RoHS) Directive 2011/65/EU as amended by Directive 2015/863/EU.

This product also is compliant with a concentration of the Substances of Very High Concern (SVHC) candidate list which are contained in a quantity of less than 0.1%(w/w) in each components of a product and/or its packaging placed on the European Community market by the BeRex and Suppliers.

NATO CAGE code:

2	N	9	6	F
----------	----------	----------	----------	----------