




# Package Outline Drawing



[END VIEW]




[SIDE VIEW]




SYMBOL	Common					
	DIMENSIONS MILLIMETER			DIMENSIONS INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.34	0.37	0.40	0.013	0.015	0.016
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	0.102 Ref.			0.004 Ref.		
b	0.25	0.30	0.35	0.010	0.012	0.014
D	1.65	1.70	1.75	0.065	0.067	0.069
E	1.65	1.70	1.75	0.065	0.067	0.069
D2	1.15	1.20	1.25	0.045	0.047	0.049
E2	0.65	0.70	0.75	0.026	0.028	0.030
E3	0.25	0.30	0.35	0.010	0.012	0.014
e	0.50 BSC			0.020 BSC		
L	0.20	0.25	0.30	0.008	0.010	0.012

- NOTES:
1. DIMENSION AND TOLERANCING CONFORM TO ASME Y14.5M-1994.
  2. CONTROLLING DIMENSIONS : MILLIMETER. CONVERTED INCH

Package Size: 1.7x1.7x0.37mm	Remarks:
Exposed Pad Size: 1.2x0.7mm	Date: 2022/07/15
PIN Pitch: 0.5mm	Title: BSW-1.7x41.7-6L-P220715v10
Number of Pad: 6	Version: Rev1.0
BeRex Confidential	 BEREX

# Land Pattern Recommendation



## NOTES:

1.All dimensions are in millimeters.

Exposed Pad Size: 1.2x0.7mm
PIN Pitch: 0.5mm
Number of Via: 2
Via diameter: 0.3mm
Exposed Pad via pitch: 0.6mm

**BeRex Confidential**

Remarks:

Date: 2021/10/18

Title: BSW-1.7x1.7-6L-LP211018

Version: Rev1.0



**BEREX**